



SDQ8



Technical Specifications

- type : 2-way hiFi Pro, sealed box
- woofer : 8" CP type
- tweeter : 1.2" silk dome neodymium
- protection : system auto-reset 1-guard
- impedance : 8Ω
- RMS power low-imp.
 AES rated : 140 Watts
 music - program : 160 Watts
 dynamic peak : (lo-cut) 380 Watts
 SPL 1 watt / 1 m : 94dB
 SPL max peak : 120dB
- Freq range : 45 - 20000 Hz
- dispersion : 120° H x 100° V
- IP rating : 24
- enclosure material : enforced PolyPlastic
- bracket included : U-type
- dimensions (h x w x d) : 375 x 280 x 240
- weight : 4,87 Kg

The SDQ8 2-way optimised bass-reflex cabinet loudspeaker offers you a high performance sound, that normally isn't associated with a relatively small cabinet.

The SDQ8 is equipped with an auto-reset protection system.

It makes the SDQ8 loudspeaker very suitable for the distribution of ambient background.

The loudspeaker comes standard with a U-type bracket.

The SDQ8 loudspeakers can be used outdoor. However, be aware of the fact that the loudspeaker terminals are not protected, the fact that this is a bass reflex housing and that the grill is made of plasticized painted metal.

This means direct exposure to rain must be avoided.